

Cisco 650-042 Exam

Volume: 75 Questions

Question No: 1

Which logical interface is the communications path between the SGSN and the Osmo GGSN?

- A. IuPS interface
- B. Gi interface
- C. Gn interface
- D. MAP interface

Answer: C

Question No: 2

What is the HLR configuration `imsi starts-with` command used for?

- A. to specify the IMSI number
- B. IMSI analysis
- C. to change the IMSI number
- D. to display point-code definition

Answer: A

Question No: 3

What is the `show alarm outstanding verbose` command used for?

- A. to view alarms and some details about each one
- B. to view some general alarm-related statistics
- C. to view alarms that have been sent to a trap manager
- D. to view a cumulative count of traps that have been sent

Answer: A

Cisco 650-042 Exam

Question No: 4

Which of the following is one of the three nodes of Cisco ASR 5000 services that comprise the Evolved Packet Core?

- A. Cisco PDSN
- B. SGSN
- C. Cisco MME
- D. Cisco GGSN

Answer: C

Question No: 5

Which criteria is used to measure the maximum rate (in bits per second) that the subscriber packets can be transmitted and received for the subscriber during the sampling?

- A. Burst size
- B. committed data rate
- C. peak data rate
- D. subscriber data rate

Answer: A

Question No: 6

Which component needs to be configured within the source context to process a nontransparent Cisco GGSN call?

- A. A Gn interface (bound to a port)
- B. an IP pool
- C. a Gi interface (bound to a port)
- D. APN definition

Answer: D

Cisco 650-042 Exam

Question No: 7

When executing the traceroute command, what is the variable count used for?

- A. to show the number of packets that were sent to the remote host for verification
- B. to show the source node that is using the assigned IP address of the node
- C. to show the IP address of the remote node
- D. to specify the number of UDP probe packets to send

Answer: D

Question No: 8

Which command verifies the ability of the system to communicate with a remote node in the network by passing data packets between them and measuring the response?

- A. Show ip arp
- B. Show ip route
- C. Monitor
- D. Ping

Answer: D

Question No: 9

Which of the following statements is true regarding traffic shaping?

- A. It provides a buffer facility for packets that have exceeded the configured limit
- B. The bandwidth enforcement can be done in the downlink only.
- C. It results in uneven throughput of traffic.
- D. Excess traffic is dropped.

Answer: A

Cisco 650-042 Exam

Question No: 10

Which context provides access to a PDN or Gi interface?

- A. accounting context
- B. source context
- C. AAA context
- D. destination context

Answer: C

Question No: 11

For which mobility management state is the location of the mobile station tracked by the serving RNC?

- A. PMM-Detached
- B. PMM-Idle and PMM-Detached
- C. PMM-Idle
- D. PMM-Connected

Answer: D

Question No: 12

How many VLAN tags may contain each physical port on an Ethernet 1000 me card?

- A. up to 124
- B. up to 1820
- C. up to 1024
- D. up to 2000

Answer: C

Question No: 13

Cisco 650-042 Exam

Which reference point supports communication between the eNodeB and the serving gateway?

- A. S1-MME
- B. SI-U
- C. S3
- D. S10

Answer: B

Question No: 14

Which two of the following are the characteristics of the high availability task(choose two.)

- A. It triggers an event to the RCT subsystem to take corrective action.
- B. It runs only on the active SMC.
- C. It is found n the management module only.
- D. It provides the system with the ability to set,Retrieve, and be notified of system configuration parameters.
- E. It is responsible for maintaining the operational state of tasks in the system.
- F. Ti is responsible for executing the recovery action for any failure that occurs in the system.
- G. It is responsible for storing data for the applications that run on the system.

Answer: A,E

Question No: 15

What is the main function of GSS FileGen?

- A. process and store the information received from the GSN system and the records that the GSS application generates
- B. generate CDR data files for billing systems that do not have a direct billing interface to a GSN system
- C. enable support for multiple GSS nodes that are clustered to provide high availability and critical