

Cisco 300-170 Exam

Volume: 60 Questions

Question No: 1

You discover that a VLAN is not enabled on a leaf port even though on EPG is provisioned. Which cause of the issue is most likely true?

- A. Cisco Discovery protocol is enabled in the interface policy group
- B. A VLAN pool is not defined under the associated physical domain
- C. The VLAN is not specified in a contract
- D. An interface policy must define the VLAN pool

Answer: B

Question No: 2

Which option are L4-L7 devices registered as on a Cisco APIC?

- A. one virtual device
- B. a cluster
- C. one physical device
- D. more virtual devices

Answer: B

Question No: 3

Which configuration is needed to extend the EPG out of the Cisco ACI fabric?

- A. Create external bridged networks
- B. Statically assign a port to EPG
- C. Apply a policy between the internal and the external EPG
- D. Extend the tenant subnet of the bridge domain out of the fabric

Cisco 300-170 Exam

Answer: B

Question No: 4

The behavior of which packet type can be controlled by selecting unicast mode or flood mode in a bridge domain?

- A. ARP
- B. unknown unicast
- C. LLDP
- D. CDP

Answer: B

Question No: 5

You deploy a Cisco Nexus 1000V Series Switch that has VXLAN support. You must ensure that baremetal servers and virtual servers can communicate.

Which technology must you implement?

- A. Cisco Nexus Cloud Service Platform
- B. A-FGX
- C. SGT
- D. VM-FEX

Answer: D

Question No: 6

You are configuration a group of web servers and you create a contract that uses TCP port 80. Which action allows an external Layer 3 cloud to initiate communication with the EPG that contains the web servers?

- A. Configure the EPG as a consumer and L3Out as provider of the contract
- B. Configure OSPF to exchange routes between the L3Out and EPG

Cisco 300-170 Exam

- C. Create a taboo contract and apply it to the EPG
- D. Configure the EPG as a provider and L30out as consumer of the contract.

Answer: D

Question No: 7

Which management interface is selected by the Cisco APIC by default if an in band management interface and an out of-band management interface exist?

- A. In-band is preferred
- B. The first configured interface is selected
- C. The interface that has the highest priority is selected
- D. Out-of band is preferred

Answer: D

Question No: 8

Which Cisco APIC health score will be affected if an EPG does not have a Bridge Domain associated with it?

- A. spine health
- B. leaf health
- C. tenant health
- D. pod health

Answer: C

Question No: 9

You have a new Cisco Nexus 7000 Series Switch that has only the default VDC configured. Which option describes the default behavior of the physical interfaces on the switch?

- A. The physical ports are divided into eight groups and the first group is assigned to the default VDC

Cisco 300-170 Exam

- B. All of the physical ports on the switch are assigned to the default VDC
- C. None of the physical ports on the switch are assigned
- D. The physical ports are divided into six groups and the first group is assigned to the default VDC

Answer: C

Question No: 10

Which action occurs first when a device that has the POAP feature boots and cannot find the startup configuration?

- A. The device locates a DHCP server
- B. The device enters POAP mode
- C. The device obtains the IP address of a TFTP server
- D. The device installs software image and a configuration file

Answer: B

Question No: 11

Refer to the exhibit:

```
n5k(config)#port-profile PGIG
n5k(config-port-prof)#speed 1000
n5k(config-port-prof)#port-profile P10GIG
n5k(config-port-prof)#inherit port-profile PGIG
n5k(config-port-prof)#speed 10000
n5k(config-port-prof)#switch access vlan 100
```

You define the port profiles as shown in the exhibit, and then you assign the P10GIG port profile to interface e1. Which option is the result of this configuration?

- A. The speed of the interface is 10 Gbps
- B. The speed of the interface is 1 Gbps
- C. The interface uses the maximum speed available for the physical interface.
- D. The speed of the interface is 100 Gbps

Cisco 300-170 Exam

Answer: C

Question No: 12

You must apply a contract to all of the EPGs in a tenant. The solution must ensure that the contract is also applied to any new EPGs that are added to the tenant. Which option must you use?

- A. the QUI
- B. the vzAny managed object
- C. the REST API
- D. a Python script

Answer: B

Question No: 13

A unicast packet enters into the front panel port of a leaf switch. The leaf switch performs a forwarding lookup for the packet destination IP address and has a miss result. Assuming default configuration, which statement about what happens next is true'?

- A. The packet is sent to the forwarding proxy in the spine switch
- B. The packet is dropped on the leaf switch
- C. The packet is sent to another leaf switch within the same bridge domain
- D. The packet is flooded across the entire fabric because it is an unknown unicast.

Answer: D

Question No: 14

You deploy AVS for Virtual Manager integration and you add a host that has five VMNICs. You must use VXLAN to maximize the load balancing of the traffic inside the fabric. How many VMKNICs must you add?

- A. 2
- B. 3