



Cisco Video Infrastructure Implementation (VII)



EXAMKILLER

Help Pass Your Exam At First Try

Total Question: 91 QAs

Question No: 1

Which troubleshooting tool does an engineer use to determine whether a cat! is being subjected to traversal bandwidth restrictions?

- A. registration log
- B. calls log
- C. search history log
- D. event log

Answer: D

Question No: 2

Which method does the Conductor use to determine the source of an incoming call to a rendezvous type conference?

- A. conference IP addresses
- B. location IP addresses
- C. management IP addresses
- D. source IP addresses

Answer: B

Question No: 3

Where in the TMS application does an engineer add individual endpoints or infrastructure to the TMS database?

- A. System > Navigator
- B. System > System Overview
- C. System > Provisioning
- D. System > Manage Dial Plan

Answer: A

Question No: 4

Cisco Meeting Server can be deployed using three different deployment models, which option lists deployment models that are the best solution to accommodate fail-over?

- A. single combined server deployment
- B. scaled and resilient server deployment
- C. scaled and combined server deployment
- D. single split server deployment

Answer: B

Question No: 5

In an H.323 call that is not interworked, which three signaling protocols are routed through the Expressway? (Choose three.)

- A. RTP
- B. Q.931

C. H.254

D. RAS

E. RTCP

F. H.245

Answer: A,E,F

Question No: 6

Which two methods can be used in TMS to schedule conferences? (Choose two.)

A. Administrative Tools > Configuration > Conference Settings

B. Booking > New Conference

C. Scheduling > New Conference

D. Reporting > Conferences

E. Monitoring > Conference Control Center

Answer: A,B

Question No: 7

An engineer wants to add a domain to a numeric E.164 alias dialed by an H.323 endpoint. Which option is the Cisco recommended method to add this domain in the Expressway configurations?

A. transforms

B. user policy

C. service preference

D. call policy

Answer: A

Question No: 8

Which option do Enterprise settings on Cisco Spark determine?

A. where user information comes from

B. how connectors are integrated in a hybrid deployment

C. bot integration

D. API integration

Answer: A

Question No: 9

Which statement about Call Service Connect on a Cisco Spark Hybrid deployment is true?

A. Call Service Connect does not require media traversal capabilities or licenses to be installed.

B. Mutual TLS can be used to deploy Call Service Connect, but it is not required.

C. Call Service Aware does not need be deployed to use Call Service Connect.

D. Call Service Connect allows integration between Cisco Spark and Cisco Unified Communications Manager.

Answer: D

Question No: 10

Which statement about setting up a call bridge cluster for a resilient and scalable Cisco Meeting Server deployment is true?

A. Call bridges can connect to databases in full mesh.

- B. Call bridges only connect to the master database.
- C. Only one call bridge should be configured per domain in a database cluster.
- D. Call bridges can read/write to any database in a cluster at anytime.

Answer: A

Question No: 11

Cisco Meeting Server uses four API commands to interact with the server. Which API command is used to modify a configuration setting on the Cisco Meeting Server?

- A. DELETE
- B. PUT
- C. POST
- D. GET

Answer: B

Question No: 12

Which two statements about the relationship between the Expressway series and the Cisco Unified Communications Manager are true? (Choose two.)

- A. The Expressway solution can be peered with a Cisco Unified Communications Manager to allow for greater capabilities.
- B. The Expressway series can never operate as a standalone call-control solution.
- C. The Expressway series requires the peering with a Cisco Unified Communications Manager to act as a call-control device.
- D. The Expressway series may operate as a standalone call-control solution.
- E. The Expressway series only supports SIP-based communications.

Answer: A,B

Question No: 13

When you write a new app in Tropo, in which format must the app scripts be saved?

- A. .xml
- B. .wav
- C. .mp4
- D. Js
- E. .json

Answer: D

Question No: 14

Which group of items must be configured when adding a Cisco Meeting Server to TMS before the server can be used in scheduled conferences?

- A. DNS address, numeric ID base, numeric ID quantity
- B. domain, numeric ID base, conference ID range
- C. MAC address, numeric ID base, numeric ID quantity
- D. domain, numeric ID base, numeric ID quantity

Answer: D

Question No: 15

Which option is a user policy?

- A. authentication
- B. admin policy
- C. call policy
- D. Find Me

Answer: B

Question No: 16

The TMS Systems > Navigator menu selection is not visible on a scheduler's computer. Which cause is the most likely?

- A. The scheduler's computer has a port blockage.
- B. NET or US is not set up on the scheduler's computer.
- C. The scheduler does not have adequate permissions associated to their log in credentials.
- D. The network has a port blockage.

Answer: C

Question No: 17

Which description of the role of the conference alias in the Cisco Conductor is true?

- A. It determines the bridge pool to be selected for a conference.
- B. The conference template determines the bridge pool to be selected for a conference.
- C. It is dialed by a user and Conductor uses that alias to determine the conference template.
- D. It selects the Expressway to be used for media traversal.

Answer: C

Question No: 18

Which option is a method for controlling bandwidth within a subzone?

- A. authentication
- B. federation
- C. do not disturb
- D. interoperability

Answer: A

Question No: 19

Which configuration on the Expressway is needed for a SIP end point to register?

- A. active neighbor zone between the end point and the Expressway
- B. SIP authentication enabled
- C. Registration restriction policy in Allow mode
- D. SIP domain

Answer: D

Question No: 20

Which two options are requirements to use OAuth access tokens with Cisco Spark? (Choose two.)

- A. Tokens must request access to servers before applications register to Cisco Spark.