

## Arista ACE-A1.2 Exam

### Volume: 99 Questions

Question No: 1

On EOS 4.13.IF, which of the following statements are true in regards to Arista's Tap Aggregation feature?

- A. Tap ports are send only.
- B. Tap ports are receive only.
- C. Tool ports are send only.
- D. Tool ports are receive only.

Answer: D

Question No: 2

Where does About look for the boot system image at boot time?

- A. At the location specified in the running-config
- B. At the location specified in the startup-config
- C. At the location specified in a file named boot-config on flash:
- D. At the location specified in a file named boot\_config on flash:

Answer: C

Question No: 3

When ZTP is in enable mode, what triggers ZTP when the switch boots?

- A. A missing or zero-byte SWI image.
- B. A missing or zero-clue administrator.
- C. A missing or zero-byte startup-config file
- D. A missing or zero-byte running-config file

## Arista ACE-A1.2 Exam

Answer: C

Question No: 4

Which of the following are valid Event Manager triggers?

- A. on-boot
- B. on-schedule
- C. on-startup-config
- D. on-reload

Answer: A,C

Question No: 5

Which of the following Arista switch series' supports Zero Touch Provisioning (ZTP)?

- A. 7050
- B. 7280E
- C. 7300
- D. 7500E

Answer: D

Question No: 6

Which command would you use to change the SSH Idle timeout after entering the 'management ssh' command?

- A. idle-timeout <minutes>
- B. timed <minutes>
- C. timeout <minutes>
- D. ssh-idle <minutes>

## Arista ACE-A1.2 Exam

Answer: A

Question No: 7

What would be the result of issuing a reload command on one of the two switches peered together in an MLAG domain where both switches are running EOS version 4.14.IF?

- A. Dual-homed hosts lose 50% of network capacity through the MLAG domain while the switch reboots
- B. The peer switch also reboots to ensure network stability.
- C. The peer switch sends out gratuitous BPDUs to let the network know that it has assumed the root bridge role.
- D. Nothing bad ever happens when MLAG is enabled!

Answer: A

Question No: 8

On an Arista switch, which port is used to connect a laptop to the switch for initial configuration or password recovery?

- A. Ethernet 1
- B. Console
- C. Management 1
- D. Ethernet 1/1

Answer: A

Question No: 9

How many Arista switches may be a part of a single MLAG domain?

- A. 2
- B. 4
- C. 8

## Arista ACE-A1.2 Exam

D. 16

Answer: A

Question No: 10

Which of the following are not valid boot-config file entries?

A. NETGW=192.168.1.1

B. IMAGE-flash:EOS-4.12.1.swi

C. SWI=flash: EOS-4.12.1.swi

D. SWIX=flash:EOS-4.12.1.swi

Answer: B

Question No: 11

What is the default spanning-tree mode on an Arista switch?

A. STP is disabled

B. PVST

C. RPVST

D. MST

Answer: D

Question No: 12

What is required in order for Multi-Switch CLI to be implemented?

A. One or more Arista products with management xmpp enabled.

B. an XMPP-based server such as EJabberd

C. an instant messaging client such as Admium or Trillian

D. an SSD drive to the extensive logging produced by this feature.

## Arista ACE-A1.2 Exam

Answer: B

Question No: 13

Which of the following statements is true with an Arista switch that has no configuration, but has booted with ZTP disabled?

- A. You may login directly as root, but only when using SSH.
- B. You may login as root, but only if you login as admin first.
- C. You can run root-level commands without a password after logging in as root.
- D. You cannot issue root-level commands until you add a user with a password.

Answer: D

Question No: 14

What Arista feature helps with the diagnosis of microbursting events?

- A. LANZ
- B. DANZ
- C. PANZ
- D. FANZ

Answer: A

Question No: 15

On what interface(s) will ZTP send out requests?

- A. Only the management interface.
- B. Only the console.
- C. All interfaces.
- D. All connected interfaces.