servicenow

CIS-Discovery

Certified Implementation Specialist - Discovery

Total Question: 78 QAs

Question No: 1

Based on this image, which of the following statements are true? (Choose three.)

Operation	Merge Table ▼

* First Table	$name_details
* Second Table	$more_process_info
* Target Table	$cmdb_ci_web_server

| Merge Criteria	Condition ▼
Meet	Any ▼ Following condition
	$process.executablePath Contains ▼ "mongoose"
Unmatched Values	Remove ▼

A. Attributes from two tables populate a table with the same name as a ServiceNow CMDB table.

B. This operation is more than likely a part of a step on a pattern set to Application Pattern Type.

C. If a value is unmatched, it is still merged into the Target Table.

D. For this operation to run, there must be some data in the process.executablePath variable.

E. This is a horizontal pattern of type "infrastructure."

Answer: B,D,E

Question No: 2

Based on the following images, which choice best describes what occurs if Discovery sets the name attribute of a discovered Windows Server CI to 'Windows1' and then Altiris discovery runs detecting 'Windows2' for the name attribute on the same CI?

Reconciliation Definitions

		Data Source	Applies to	Attributes	Active
☐	ⓘ	Altiris	Windows Server [cmdb_ci_win_server]	name	true
☐	ⓘ	OpenView	Windows Server [cmdb_ci_win_server]	name	true
☐	ⓘ	ServiceNow	Windows Server [cmdb_ci_win_server]	name	true

All — 1 to 3 of 3

Data Source Precedentes

New Go to Order ▾ Search

All — 1 to 3 of 3

		Applies to	Data Source	Order ▲	Active
☐	ⓘ	[cmdb_ci_win_server]	ServiceNow	100	true
☐	ⓘ	[cmdb_ci_win_server]	OpenView	200	true
☐	ⓘ	[cmdb_ci_win_server]	Altiris	300	true

A. The name of the CI stays 'Windows1'.
B. The name of the CI changes to 'Windows2'.
C. The name of the CI does not populate with either discovery.
D. The CI is not discovered because Discovery is not listed in either image.
Answer: B

Question No: 3
For the Parse Variable pattern operation, what is required to have two different parsing methods to populate variables?
A. Two different Debug Mode sessions.
B. A tabular and a scalar variable.
C. Two different steps.
D. Two different Define Parsing selections on the same step.
Answer: D

Question No: 4

Which best describes Discovery schedule of type Configuration Item?

A. Verifies Configuration Item data from the scanned IP ranges against the data in the CMDB.

B. Creates only a list of discovered IPs in both IPv4 and IPv6 formats.

C. Collects complete information from the scanned IP ranges and sends it to the CMDB.

D. Directly populates records in the assets table.

Answer: D

Question No: 5

When installing a MID Server on a Windows platform, which right must be associated when creating a Service Account?

A. Root

B. Domain Admin

C. MID Server User Role

D. Log on as service

Answer: C

Question No: 6

Which of the below choices are needed for Quick Discovery? (Choose two.)

A. MID Server

B. Discovery Schedule

C. PID

D. Target IP

Answer: A,B

Question No: 7

In order to use Debug from the Pattern Designer, you must have what?

A. a proxy server

B. a discoverable CI

C. the admin role

D. Service Mapping installed

Answer: D

Question No: 8

A discovery runs against a Windows Server returning the following attribute values for the first time:

name = WindowsSN1

serial_number = 12321

A subsequent discovery is ran against a different Windows Server returning the following attribute values:

name = WindowsSN2

serial_number = 12321

With only base system CI Identifiers configured, which of the following is true?

A. A Windows Server CI is created, then updated with WindowsSN2 as the name.

B. Two Windows Sewer CIs are created, with WindowsSN1 AND WindowsSN2 for names.

C. Two Windows Server CIs are created, without serial_number values.

D. A Windows Server CI is created, then updated with WindowsSN1 as the name.

Answer: C

Question No: 9
Which choice represents the three best ways of extending Discovery?
A. Orchestration, Classifiers, Discovery Patterns
B. Fingerprinting, Classifiers, Discovery Patterns
C. Orchestration, Classifiers, Probes & Sensors
D. Classifiers, Probes & Sensors, Discovery Patterns
E. Classifiers, Fingerprinting, Probes & Sensors
Answer: E

Question No: 10
SNMP Credentials require which of the following?
A. write community strings
B. usernames
C. read community strings
D. port 135 access
Answer: C

Question No: 11
Which choice will populate the Location field for a discovered CI?
A. Location field for a Discovery Schedule
B. Location field for a parent CI Type
C. Location field for a Port Probe
D. Location report from the Discovery Dashboard
Answer: A

Question No: 12
What role is needed by the MID Server's user account to interact with a ServiceNow instance?
A. mid_server
B. discovery_admin
C. sm_mid
D. mid_discovery
Answer: A

Question No: 13
Which operation is used to change from the default credentials to any other appropriate credentials in a horizontal pattern?
A. Change credentials
B. Change user
C. Alternate credentials
D. Alternate user
Answer: B

Question No: 14

After navigating to an Automaton Error Messages list from Discovery > Home, how are the options on the right navigation pane categorized? (Choose two.)

A. SELECT ALL

B. SELECT ONE

C. ACTION ON SELECTED

D. ACTION ON ALL

Answer: A,D

Question No: 15

Which of the following can be used in the Debug Identification Section in Debug Mode for an infrastructure pattern? (Choose two.)

A. IP

B. AWS Endpoint

C. PID

D. Host Name

Answer: A,D

Question No: 16

With multiple CI data sources, which choice is the best for determining which source can update a CI attribute?

A. Business Rules

B. Data Certification

C. Transform Maps

D. Reconciliation Rules

Answer: D

Question No: 17

Which method for deleting specific CIs is not discovered in 30 days?

A. Scheduled Job

B. UI Policy

C. Service Mapping

D. Data Policy

Answer: D

Question No: 18

Which of the following choices must be installed on a MID Server to run Credential-less Discovery?

A. Credential-less Extension

B. Nmap

C. Advanced IP Scanner

D. Defender

Answer: B

Question No: 19

A network device has both an SSH port and an SNMP port open. Discovery tries the SSH probe first and it