

EMC E20-624 Exam

Volume: 65 Questions

Question No: 1

What is a benefit of using TimeFinder SnapVX?

- A. Orphaned snapshots
- B. No logical volume number is used
- C. Fan-in for efficiency
- D. High impact point-in-time copies

Answer: D

Question No: 2

What is the maximum distance from System Bay 1 that a dual engine bay can be dispersed in a VMAX3 array configurations?

- A. 15 meters
- B. 20 meters
- C. 25 meters
- D. 30 meters

Answer: C

Question No: 3

What is the maximum number of standard storage bays that can be part of a VMAX 20K or 40K?

- A. 6
- B. 8
- C. 10
- D. 12

EMC E20-624 Exam

Answer: D

Question No: 4

What is the maximum number of drives supported by a VMAX 20K and 40K high density storage bay?

- A. 120
- B. 200
- C. 240
- D. 400

Answer: D

Question No: 5

Which directory is used on the user laptop, in which the SymmWin script file "CreateProc.smp" is copied into, to install the Symmetrix Procedure Generator?

- A. symmwin\user
- B. symmwin\bin
- C. symmwin\newcode
- D. symmwin\scripts

Answer: B

Question No: 6

What is used for vaulting on a VMAX3?

- A. Flash 1/0 Modules
- B. 900 GB 15K disks
- C. 2 TB 7200 RPM disks
- D. 300 GB 10K disks

EMC E20-624 Exam

Answer: A

Question No: 7

Which component of a 60-drive DAE can the VMAX3 array back-end module of a given director be cabled?

- A. LCC
- B. MIBE
- C. ICM
- D. SIB

Answer: A

Question No: 8

On a VMAX 10K (987), which DAEs support daisy chaining?

- A. 1, 2, 3 and 4
- B. 1, 2, 5 and 6
- C. 3, 4, 7 and 8
- D. 5, 6, 7 and 8

Answer: D

Question No: 9

Which VMAX3 system bay component uses violet color-coded cables?

- A. InfiniBand Fabric Switch B
- B. Ethernet Switch B
- C. Ethernet Switch A
- D. Point of Service WorkTray

EMC E20-624 Exam

Answer: B

Question No: 10

What accurately describes the planning and configuration considerations for Flash drives in a VMAX environment?

- A. Spares do not count towards the minimum number of HDD spares
- B. Flash drive spares count towards the minimum number of HDD spares
- C. Sparring is not supported using Flash drives
- D. A minimum of two spares for 1 to 32 Flash drives, per drive type

Answer: A

Question No: 11

What is the normal status of an R2 device on a VMAX3?

- A. Not Ready
- B. Split
- C. Read/Write
- D. Write Disabled

Answer: C

Question No: 12

A VMAX3 running HYPERMAX OS has several internal emulations. Which functions will the IM emulation perform?

- A. Manage and monitor internal memory
- B. Manage communications between the back-end and front-end
- C. Execute infrastructure tasks
- D. Internally manage SRP resources

EMC E20-624 Exam

Answer: C

Question No: 13

Which method is used to gather STP data from a VMAX3?

- A. Navisphere
- B. SymmWinn
- C. vAPP Manager
- D. Solutions Enabler

Answer: D

Question No: 14

A customer wants to create a large number of TimeFinder SnapVX snapshot sessions that will be host accessible. However, they are concerned about the remaining space in their Storage Resource Pool. Which type of link should be created?

- A. Undefined
- B. Copy
- C. Defined
- D. NoCopy

Answer: D

Question No: 15

Which VMAX3 model(s) has a maximum cache, per engine, of 2 TB and supports a maximum of 28802.5" drives?

- A. VMAX 100K
- B. VMAX 200K only
- C. VMAX 200K and VMAX 400K