

## **Nokia NCS 2002252020 Exam**

**Volume: 85 Questions**

Question No : 1

When ODB-BAOC is active for a subscriber, which entity performs the Barring for MOC Calls?

- A. MSS
- B. HLR
- C. MS
- D. SCP

Answer: A

Question No : 2

X3 interface is used for:

- A. CDR transfer
- B. Administrative interface to LIC
- C. Transmission of call related/unrelated information to LIC
- D. Transmission of call content to LIC

Answer: D

Question No : 3

In the process of KPI monitoring, which items need to be planned and decided?

- A. KPI list.
- B. Tools to be used.
- C. Measurement activation.
- D. All the above.

Answer: D

## **Nokia NCS 2002252020 Exam**

Question No : 4

X1 interface is used for:

- A. CDR transfer
- B. Administrative interface to LIC
- C. Transmission of call related/unrelated information to LIC
- D. Transmission of call content to LIC

Answer: B

Question No : 5

In MOCN, which configuration is used by RAN node to keep UE served by the same selected CN operator pool?

- A. IMSI
- B. TMSI
- C. NRI
- D. TLLI

Answer: C

Question No : 6

What is the maximum number of MSSs in one pool supported by Nokia MSS?

- A. 5
- B. 7
- C. 10
- D. 15

Answer: C

## **Nokia NCS 20022252020 Exam**

Question No : 7

MGW Multiple Isolated IP Networks feature is NOT supported for:

- A. Nb Interface
- B. Nb' Interface
- C. ATM Interface
- D. AoIP Interface

Answer: C

Question No : 8

What is the interface between VLR backup server and MSS?

- A. Sz
- B. SGs
- C. Sv
- D. Mc

Answer: A

Question No : 9

What is the first document delivered for CS Core Design project?

- A. HLD
- B. LLD
- C. DLD
- D. Datafill

Answer: A

Question No : 10

## **Nokia NCS 20022252020 Exam**

Which input is required to design the bayface layout of OpenMGW?

- A. BOM (Bill of material).
- B. OTOCs Tool
- C. Site connectivity guidelines.
- D. Design capacity of MSS/MGW.

Answer: A

Question No : 11

MSRN received from HLR can be analyzed in Tree defined in:

- A. EOS or EOS Attribute Analysis or SPR HLR Enquiry
- B. Only EOS cause code 1009 or EOS Attribute Analysis
- C. PRFILE
- D. EOS, EOS attribute Analysis or Routing attribute Analysis

Answer: A

Question No : 12

Which tool could be used to dimension the various interfaces of Open MSS?

- A. OTOCS
- B. MSSPLAT
- C. Load tool
- D. Interface planning tool

Answer: A

Question No : 13

In SS7 protocol suite, which layer performs Routing on Label (OPC, DPC)?

## **Nokia NCS 20022252020 Exam**

- A. MTP3
- B. SCCP
- C. MTP1
- D. MTP2

Answer: A

Question No : 14

JUMP pages are used for?

- A. Jitter measurements.
- B. KPIs and Counters definitions/descriptions.
- C. Traffic measurements.
- D. Latest software downloads.

Answer: B

Question No : 15

What is the measurement used to calculate the BHCA per MSS?

- A. Traffic category measurements
- B. Circuit group measurements
- C. UPD measurements
- D. CGR to destination measurements

Answer: A

Question No : 16

In OTOCs tool, the recommended TCU utilization is:

- A. 80% for both IPA and ATCA MGW